

TECHNICAL DATA SHEET

EP-FLOORSEALER

Revision Date: 26/08/2025

Publication Date: 30/06/16

EP-FLOORSEALER is for optimizing adhesion between, among other things, concrete, stone, board, steel, mortars and coatings. Apply epoxy mortars in the adhesive epoxy impregnation primer.

PRODUCT INFORMATION

| | |
|----------------------------------|---|
| Type of paint | 2-component epoxy impregnation with polyamide adduct curing agent |
| Finish | Clear |
| Density | 1.0 kg/L |
| VOC (Volatile Organic Compounds) | None |
| Flashpoint | >60°C |

DRYING TIMES

| | 20°C | 10°C |
|-----------|---------|---------|
| Dust free | 3 hours | 6 hours |
| Dry | 4 hours | 8 hours |

APPLICATIONS-INSTRUCTIONS

| | |
|-------------------------|--|
| Mixing Ratio: | Volume: comp A. – comp. B 75:25 |
| Mixing instructions: | Carefully mix both components After mixing, the primer is ready for use |
| Induction time: | non |
| Pot-life: | approx. 12 hours at 20°C |
| Application conditions: | The temperature must be above 5°C during processing |
| Application: | Use undiluted with the gun, roller or brush |
| Tool Cleaning: | Thinner EP |

DURABILITY

At least 12 months, provided that it has been stored in closed original packing at a dry and cool spot.

PACKAGING

1 L + 0,25 L 4 L + 1 L 16 L + 4 L

These data have been drawn up to the best of our knowledge and were correct at the data of issue. However we cannot accept full responsibility, because the choice of products and circumstances during elaboration of the systems fall outside our judgement. This documentation sheet will not automatically be replaced in case of modification.